



EFFICIENCY SCREW AIR COMPRESSOR

SCREW AIR COMPRESSOR TANK MOUNTED WITH AIR DRYER AND FILTER



Model	Motor power		Free air deliver	Free air deliver	Discharge pressure	Noise level	Tank volume	Electricity	Weight	Dimension
	(KW)	(HP)	(m3/min)	(CFM)	(MPa)	(dB)	(L)	(V/ph/Hz)	(KG)	(mm)
FB-7.5DT	5.5	7.5	0.85	30	0.7	55±2	300	380/3/50	415	1900*720*1470
			0.75	27	0.8					
FB-10DT	7.5	10	1.2	42	0.7	65±2	300	380/3/50	420	1900*720*1470
			1.1	39	0.8					
			0.9	32	1.0					
FB-15DT	11	15	1.6	57	0.7	65±2	300	380/3/50	465	1900*720*1600
			1.5	53	0.8					
			1.3	46	1.0					
FB-20DT	15	20	2.5	88	0.7	65±2	300	380/3/50	510	1900*720*1600
			2.3	81	0.8					
			2.1	74	1.0					

SCREW AIR COMPRESSOR WITH TANK MOUNTED



Model	Motor power		Free air deliver	Free air deliver	Discharge pressure	Noise level	Tank volume	Electricity	Weight	Dimension
	(KW)	(HP)	(m3/min)	(CFM)	(MPa)	(dB)	(L)	(V/ph/Hz)	(KG)	(mm)
FB-5.5T	4	5.5	0.85	30	0.7	55±2	300	380/3/50	415	1900*720*1470
			0.75	27	0.8					
FB-7.5T	5.5	7.5	0.85	30	0.7	55±2	300	380/3/50	415	1900*720*1470
			0.75	27	0.8					
FB-10T	7.5	10	1.2	42	0.7	65±2	300	380/3/50	420	1900*720*1470
			1.1	39	0.8					
			0.9	32	1.0					
FB-15T	11	15	1.6	57	0.7	65±2	300	380/3/50	465	1900*720*1600
			1.5	53	0.8					
			1.3	46	1.0					
FB-20T	15	20	2.5	88	0.7	65±2	300	380/3/50	510	1900*720*1600
			2.3	81	0.8					
			2.1	74	1.0					



CE European Union standard certification

Fusion's product design, production meet the standard of European Union.



ISO9001 Quality Standard

From design, manufacture to delivery, Fusion Compressor abides by the ISO9001 quality system.



Energy-saving, high efficiency and high level quality